

# Introducing the SpinCat™ SC-287™

**Engineered Specifically for Downhole Cleaning and the Removal of Plugs, Scale and Failed Linings**

- **Self-Rotating Assembly**
- **Simple Field Maintenance**
- **Fluoro-Elastomer Seals**
- **Replaceable Jets**



**SpinCats™** are designed specifically for coil tubing units.

**NEW**

**SC-287™**

## Our Newest Member of the SpinCat™ Family

The **SC-287™** is the newest member of our **SpinCat™** family. Armed with a viscous fluid governor to control rotation speed this tool uses fewer jets, thereby maximizing jet power. Larger, slower jets actually produce harder-hitting cleaning power. Whether your deposits are parafin, asphaltine, hydrates, calcium carbonate, barium sulphate or mineral scale, **SpinCat™** tools are ready to restore production without damaging the well pipe.

<b>SpinCat™ SC-287™</b>	
<b>Model</b>	<b>SC-287™</b>
<b>Max. Pressure</b>	5,000 psi 340 bar
<b>Flow Range</b>	1.0 - 3.0 bpm
<b>Flow Rating</b>	7.5 Cv
<b>Outside Diameter</b>	2.87 in 73 mm
<b>Length Overall</b>	15.6 in. 396 mm
<b>Inlet</b>	2-3/8 PAC
<b>Rotation Speed</b>	80-150 rpm
<b>Weight</b>	20 lbs 9.1 kg
<b>PSI Loss @ 1 bpm</b>	31 psi 2 bar
<b>Max. Temperature</b>	390° F 200° C



The four **SpinCat™** models range in diameter from 1.68" to 2.87".

[www.hydropulsion.com](http://www.hydropulsion.com)

U.S. Patent No. 5,909,848  
European Patent 1,068,021

**Proud Distributors of StoneAge® Waterblast Tools**

**Hydropulsion**

154 Forest Avenue  
Aberdeen, AB15 4UN • Great Britain  
Phone +44 (0) 1224 200125 • Fax +44 (0) 1224 51501  
b.storie@hydropulsion.com • [www.hydropulsion.com](http://www.hydropulsion.com)